



SOLUTIONS

SEALERS FOR STONE & TILE
The Next Generation of Stone Care Products

NATIONAL PH: 1300 4 STONE

Ph. + 61 7 5437 7714

Fax: + 61 7 5437 7715

E: info@solutionssealers.com.au

W: www.solutionssealers.com.au

ABN: 25 128 656 082

Manufacturers of BIO-SAFE Technology

Application Data Sheet:

SILACRYL

WET LOOK & MATT FINISH



APPLICATION:

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** and allow a 24 hour cure time to determine the ease of application and desired results for both stain resistance and appearance that will meet YOUR requirements.
- Remove all dirt, oil, wax, stains, dust, efflorescence, grout haze and flaking material. Ensure any acid or detergent used is hosed off completely.
- Allow newly laid concrete to cure for at least 28 days prior to application.
- If an unsealed surface has been wetted, allow 24 hours prior to sealing.
- Stir well before use.
- Use a brush, broom, spray or lambs wool applicator.
- Apply two to three coats depending on the finish required and the porosity of the substrate.
- For dense surfaces or where slate is laminating the first coat of **SILACRYL** should be broken down with 50 % **EVERSOL** or **TOLUOL**. This will improve the penetration and subsequent adhesion.
- Application should not be done when temperature is >30°C.
- **SILACRYL** is designed to seal and protect and may increase the tendency to slip on some surfaces especially when wet. Test and add '**GRIP ENHANCER**' to the final coat if required.

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product **PROVEN** defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*