



SOLUTIONS

SEALERS FOR STONE & TILE
The Next Generation of Stone Care Products

NATIONAL PH: 1300 4 STONE

Ph. + 61 7 5437 7714

Fax: + 61 7 5437 7715

E: info@solutionssealers.com.au

W: www.solutionssealers.com.au

ABN: 25 128 656 082

Manufacturers of BIO-SAFE Technology



Technical Data Sheet:

SUPER SEAL

GROUT & TILE SEALER

Description:

SUPER SEAL is not just convenient to use – it is a great **nanotechnology** sealant to aid against stains, mildew and mould. Whether it's the grout or the tiles in a shower, classic marble or granite bench tops or even terracotta pots in the garden – **SUPER SEAL** will give premium, lasting protection to make ongoing cleaning a breeze.

Advantages:

- State-of-the-art **nanotechnology** stain protection
 - Invisible sealer won't change the grout or tile colour
 - Breathable sealer won't trap moisture behind tile or grout
 - No lengthy delays for grout to cure before sealing
 - Prevents mould and mildew
 - Doesn't go yellow in the sun or milky when wet
 - Hard-wearing sealer which makes cleaning of grout & tiles easier
-

Characteristics:

Colour:	Clear
Weight	0.80
Solvent	Acetone
DG Class	2
U.N Number	1950
Coverage	10 - 18 sq m per can (depending on surface porosity)

Recommendations:

Grout
Polished Porcelain
Granite
Marble
Terracotta
Most Ceramic Tiles

Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user MUST educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*

Solutions - Sealers Technical service department Doc: SUPER SEAL TECH DATA.VER.2