



Manufacturers of BIO-SAFE Technology

## Technical Data Sheet:

# HI-LACRYL

## COLOUR HI-LIGHTER



### Description:

**HI-LACRYL** is an extra tough clear acrylic sealer especially designed for concrete and sandstone. Excellent resistance to heavy wear and ultra violet rays makes **HI-LACRYL** ideal for external areas, paths, patios and pool surrounds. **HI-LACRYL** is designed for a mild highlighting effect to enhance/darken the natural color of the surface.

### Advantages:

- Suitable for internal and external use.
- Penetrates deeply for excellent wearing under heavy traffic.
- Low solids content for slight breathability in porous substrates.
- Gives surface a darkening effect and enhances the natural colors of the surface.
- Seals lime dust into concrete to prevent leaching and a constant need for sweeping.
- Is easy to reseat without stripping.
- Does not yellow externally.
- Australian owned and manufactured in Australia.

### Characteristics:

Colour:	Clear
Weight:	0.90
Solvent:	Hydrocarbon
DG Class:	3
U.N Number:	1263
Coverage:	5 – 8 sq m per lt (depending on porosity)

### Recommendations:

Sandstone  
Exposed aggregate  
Plain concrete  
Concrete Pavers  
Stamped Concrete  
Stencil Concrete

#### Disclaimer – User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*